



Enlarge 

**LOCATE a dealer** 

Enter your  
Zip Code

Printer-Friendly Format 

Bookmark this Page 



## MX-M550 | Copiers

### Specifications

<b>Copying Speed</b>	55 cpm (8.5" x 11")
<b>Automatic Duplex</b>	Standard- unlimited
<b>Original Size</b>	Max. 11" x 17"
<b>Paper Feed</b>	Dual Tray: 2,000-sheets, 16-28 lb. Bond (8 1/2" x 11" only) Tray 3 & 4: Size adjustable; 500-sheets, 16 lb. Bond to 110 index Bypass Tray: 100-sheets, 14 lb. Bond to 110 lb. index Optional Large Capacity Tray: (AR-LC6 or AR-LC7)
<b>Print Speed</b>	55 ppm (8.5" x 11")
<b>Page Description Language</b>	PCL5e, PCL6, Postscript Level 3 (option)
<b>Modem / Transmission Speed</b>	33.6 Kbps (optional)
<b>Type</b>	Console
<b>Copy System</b>	Dry, electrostatic transfer system
<b>Originals</b>	Sheets, bound document, photographs
<b>Original Size</b>	Max. 11" x 17" / Min. 5.5" x 8.5"
<b>Copy Size</b>	Max. 11" x 17" / Min. 5.5" x 8.5"
<b>Continuous Copy</b>	Max. 999 copies
<b>Copy Ratio</b>	25% to 400%
<b>Fixed presets</b>	8 preset ratios
<b>Resolution</b>	600 dpi
<b>First-Copy Time</b>	3.9 seconds or less
<b>Warm-Up Time</b>	120 seconds or less
<b>Original Feed System</b>	Duplex Single-Pass Feeder
<b>Hard Drive</b>	40GB

- Get Service
- Get Literature
- FAQs
- Special Offers
- Register
- Warranties
- Press Releases

- Manuals
- Awards
- Software
- Downloads
- Supplies
- Corporate Sales
- Dealer Resources

- Document Applications

Detailed Specs



go 

### Browse our Products

-  Appliances
-  Business
-  Entertainment
-  Mobile
-  Solar Power

### Product Registration

### Sharp Support Center

Easily locate the support you need for your Sharp product

### Corporate Sales & Partnerships

Information for Dealers & Corporate Clients

### About Sharp

View Press Releases, Special Offers & Career Information

<b>Fusing System</b>	Heat rollers
<b>Developer System</b>	Magnetic Brush Development
<b>Exposure System</b>	OPC
<b>Light Source</b>	Halogen lamp
<b>Gradation</b>	256 levels
<b>Required Power Supply</b>	120 volts, 60Hz, 16A
<b>ENERGY STAR®</b>	Yes <sup>1</sup>
<b>Weight - base unit</b>	Approximately 408 lbs.
<b>Dimensions (w x d x h) - base unit including doc feeder</b>	28.7" x 26.7" x 46.9" (main unit)
<b>Optional Equipment</b>	Optional saddle-stitch finisher, optional hole punch unit ; optional post-sheet inserter finisher; 2-tray sorting/stapling finisher; Fax Expansion Kit; 3,500 Large Capacity Paper Deck; Network Scanning Kit; PostScript 3 (emulation); Bar Code Font Kit
<b>Printer Specifications</b>	
<b>Technology</b>	Embedded Sharp controller w/network interface (standard)
<b>Processor</b>	64 bit RISC, 600 Mhz
<b>Print Size</b>	Max. 11" x 17"
<b>Resolution / Print Quality</b>	600 dpi, 1,200 x 600 dpi with smoothing
<b>Interface</b>	USB 2.0 port
<b>Network Operating Systems</b>	Windows 95/98/Me, 2000, XP, Vista, 2003 Server, Server 2003 x64, XP x64, Vista x64 (GPD only); Mac OS 9, OSX (PPD only). <sup>2</sup> Note: Postscript 3 kit required for Macintosh support.
<b>Protocols</b>	IPX/SPX, TCP/IP (IPv4, IPv6, IPsec (LPD)), Net BEUI, EtherTalk <sup>2</sup>
<b>Auto Switching</b>	Yes

<b>Print Driver Support</b>	Windows 95/98/Me, 2000, XP, Vista, 2003 Server, Server 2003 x64, XP x64, Vista x64 (GPD only); Mac OS 9, OSX (PPD only). <sup>2</sup> Note: Postscript 3 Kit required for Macintosh support
<b>Resident Fonts</b>	80 fonts for HP PCL, 136 fonts for PS (with optional AR-PK5)
<b>Memory</b>	128MB (standard); expandable to 384MB (using AR-SM5 option)
<b>Print Paper Feed</b>	Standard Duplex Single-Pass Feeder
<b>Fax Specifications</b>	
<b>Type</b>	PSTN, PBX
<b>Document Feeder</b>	Standard Duplex Single-Pass Feeder
<b>Original Size</b>	Max. 11" x 17" / Min. 5.5" x 8.5"
<b>Print Size</b>	Max 11.5" max (11"x17" printing)
<b>Transmission Speed</b>	2 seconds (Super G3); 6 seconds (G3) <sup>3</sup>
<b>Broadcast</b>	Up to 500 destinations
<b>Rapid and Group Dial</b>	Combined total of 500 one-touch and group keys
<b>Speed Dial</b>	Combined total of 500 one-touch and group keys
<b>Grayscale</b>	256 grayscale levels
<b>Fax Memory</b>	2MB standard expandable to 10MB
<b>Scanning Specifications</b>	
<b>Resolution</b>	200, 300, 400,600 dpi Email/FTP resolution
<b>Compatibility</b>	TWAIN compliant (push out method)
<b>Sharpdesk™ licenses</b>	10-user licenses included with Network Scanner Expansion Kit

Product specifications and design are subject to change without notice.

<sup>1</sup>Sharp has determined that this product meets the ENERGY STAR® guidelines for energy efficiency. ENERGY STAR is a U.S. registered mark.

<sup>2</sup>Data Security Kit, Windows Vista/x64 Drivers, IPsec, SMTPS and FTPS Support available Spring 2007.

<sup>3</sup>Based on ITU-T test chart #1 at standard resolution in Sharp special mode. Actual transmission time may vary depending on line conditions.

[BACK TO TOP](#) 

---

© 2009 Sharp Electronics Corp.

[sitemap](#) [legal](#) [privacy](#)

Sharp and AQUOS are registered trademarks of Sharp Corporation.  
All other marks are the property of their respective holders.